



HARDWOOD FLOORING | TECHNICAL INFORMATION



Product # 2-1179-3668



LINE | METROPOLITAN GREY
COLOR | STEEL

Wood species | Oak
Grade | 1 Natur
Constructions | 2-layer T&G Engineered Flooring
Size | 15,0 x 190 x 600...2100 mm (5/8" x 7 1/2" x 2'..7")
Finish | Resilient Lacquer

CONSTRUCTION : 2-LAYER T&G ENGINEERED FLOORING

DIMENSIONS :			PACKAGING :		
			BOX	PALLET	
Thickness	15,0 mm (5/8")		Content:	2,26m ²	40 (90,4m ²)
Width	190 mm (7 1/2")		Weight	26 kg	1050 kg
Length	600...2100 mm (2'..7')		H x W x L	101 x 225 x 2150 mm	1134 x 905 x 2160 mm
Average length	1,19 m (4')		Content:	24,5 sq.ft.	973 sq.ft.
Microbevel	0,5 mm		Weight	57 lb	2345 lb
Joint type	tongue and groove (T&G)	H x W x L	4" x 9" x 85"	45" x 36" x 85"	

DEVIATIONS :		
Deviation on Thickness	± 0,2 mm	
Deviation on Width	± 0,2 mm	EN 13489
Height Difference	≤ 0,2 % of width	ГОСТ 862.3 - 2020
Cup	≤ 0,2 % of plank width	ГОСТ 862.1 - 85
Bow	≤ 0,1 % of length	
Spring	≤ 0,5 % of length	EN 13489

CHARACTERISTICS :		
Fire resistance	Dfl-s1	
Formaldehyde emission class	E1	
Pentachlorophenol content	None	EN 14342
Thermal penetration	0,104 m ² ·K/W	
Thermal conductivity	0,154 W/(m·K)	
Structural warranty	Lifetime	

INSTALLATION :	STORAGE AND USAGE :
<p>Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.</p>	<p>— Air humidity 40% – 65% — Temperature +18 °C – +22 °C</p>

FINISH : RESILIENT LACQUER

DESCRIPTION :	
Type of coating	UV-cured modified polyurethane-acrylate
Surface (finish) type	Semi-closed pores
Sheen	Semigloss 15 - 22 GU/60°
Finish warranty	-

CLASSIFICATION SURFACE CHARACTERISTICS :		
Wear resistance	Not rated	EN 438-2
Scratch resistance	Not rated	EN 438-2
Slip resistance	52 (SRV dry)	EN 15676
Resistance to chemical agents	Class 5 (Except blue ink)	EN 13442
Repairability	Medium	

MAINTENANCE AND CARE CONDITIONS :

Maintenance of hardwood floors with Resilient Lacquer finish assumes regular (daily if necessary) cleaning from dust and dirt using a vacuum, followed by a thorough cleaning using Coswick hardwood floor cleaner or other similar product.

GRADE : 1 NATUR

DESCRIPTION :		DESCRIPTION :	
Sound sapwood	Permitted non-contrasting up to 25% of the plank area	Bark pocket	Permitted up to 50 mm in length, up to 5 mm in width, filled
Slight color variation	Allowed	Pith	Permitted
Knot	Permitted up to 25 mm, filled	Slope of grain	Permitted
Checks	Permitted filled up to 0,5 mm in width	Medullary ray	Permitted